



NEWLOOK

Newlook International, Inc. Eco Acid™

Technical Information Sheet

Newlook International, Inc. Eco Acid™ is a water-based, non-corrosive concrete etching and profiling compound. It is an effective, non-fuming alternative to harsh acids, such as muriatic acid. Eco Acid is environmentally friendly, non-toxic, non-hazardous, and it safely prepares concrete surfaces by opening up the pores for effective staining. Eco Acid can be used with Newlook, International, Inc. Concrete Color Stains™ or any other penetrating concrete color stain.

USES AND BENEFITS

- Use Eco Acid to etch or profile unsealed concrete flatwork, concrete block, pavers, and imprinted concrete.

PREPARATION PRIOR TO APPLICATION

- All debris, alkali, curing compounds, loose concrete, coatings, dirt, paints, oils, release, sealers, or any foreign materials that would prevent Eco Acid from making contact with the concrete surface must be removed (Including "cure and seal" products).
- Preparing the concrete properly ensures that Eco Acid will effectively react with the concrete.

APPLICATION PREREQUISITES

- Newlook International, Inc. strongly recommends representative jobsite samples
- Protect any walls and adjacent areas where etching is not desired. Plastic or visquene is recommended.
- Saturate plants, shrubs, and grass adjacent to cleaning area with water before, during, and after use.
- Ensure that any product or rinse water runoff is properly contained.
- The concrete surface may be damp, but any standing water should be removed before application.

APPLICATION OF ECO ACID

- Eco Acid is intended to be used as provided and NOT diluted.
- Apply with an applicator brush.

- Broom until evenly applied.
- Allow dwell time of 15 to 30 minutes.
- Broom occasionally.
- In hot, sunny, or windy conditions, the product may dry prematurely. Mist with water as needed to reactivate the product.
- Hard troweled, dense, or hardened surfaces may require a second application with dwell time increased to at least 30 minutes.
- When finished, flush the surface thoroughly with clean water to ensure that no residue remains.

STORAGE

- Store in original container in areas inaccessible to children and pets.
- Keep containers tightly sealed.
- Do not reuse empty container. Rinse empty container and replace cap before discarding.
- DO NOT allow product to freeze.

LIMITATIONS

- Eco Acid is not effective on sealed surfaces.
- Avoid prolonged contact with concrete surfaces that should not be etched.

CAUTION

KEEP AWAY FROM CHILDREN AND ANIMALS. Before using or handling, read the MSDS and Product Instructions. DO NOT CONSUME. Avoid contact with eyes and skin. Wear rubber gloves, aprons and safety eye goggles. Use good hygiene when handling this product. It is recommended that you wash and bathe after each use.

PACKAGING AND COVERAGE

Kit Type	Bucket Size	Coverage (Sq Ft.)
Eco Acid	5 Gallon	200 Sf. Per Gallon (4.9 m ² /L) per application
	1 Gallon	200 Sf. Per Gallon (4.9 m ² /L) per application

WARRANTY

Newlook International, Inc. Eco Acid ("Product") are not intended for public use and are intended for use by licensed contractors and installers, experienced and trained in the use of these products. Product is warranted to be of uniform quality within manufacturing tolerances. The manufacturer has no control over the use of Product, therefore no other oral or written representation or statement of any kind, express or implied, now or hereafter made is authorized or warranted by Newlook International, Inc. or its affiliates, and Newlook International, Inc. and its affiliates hereby disclaims all such warranties, including those of merchantability or fitness for a particular purpose. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven to be defective. Newlook International, Inc. shall not be liable for special, incidental, or consequential damages, including delays or lost profits. Communication of this warranty and its limitations to end users is not the responsibility of Newlook International, Inc. but should be communicated by those in direct contact with the end user. Any claim regarding product defect must be received in writing within one year from the date of manufacture. No claim will be considered without such written notice or after the specified time interval. The end user shall be responsible for determining Product's suitability and assumes all risks and liability.

NEWLOOK INTERNATIONAL, INC. ECO ACID™

Suggested Short Form Specification:

All concrete flatwork designated to be etched and profiled with an environmentally friendly, non-corrosive acid-etching compound in the plans and specifications shall be profiled with *Eco Acid*, distributed by Newlook International, Inc., Salt Lake City, UT, 877-763-9566 in accordance with the Newlook International, Inc. Eco Acid Technical Information Sheet and a minimum of ____ kit(s) per average of 200 square feet per application.

NEWLOOK INTERNATIONAL, INC. PRODUCTS available through: